

Technical Data Sheet of VAE Emulsion CW40-916

Product name: Vinyl Acetate-Ethylene Copolymer Emulsion CW40-916

CAS NO.: 24937-78-8

Technical Data of VAE Emulsion CW40-916

Items	Specifications
Appearance	White emulsion or light yellow and free of suspended matter
Solid content(%)	≥54.5
Viscosity(mpa.s, 25°C)	3300~4500
pH	4.0-6.5
VAC(%)	≤0.20
Ethylene(%)	15.0-19.0
Free Formaldehyde(g/kg)	≤0.02
Glass transition temperature (Tg/°C)	3~5
Minimum film formation temperature(°C)	<0

Application:

1. Versatility: VAE Emulsions Are Highly Versatile And Can Be Tailored To Meet Specific Requirements In Different Industries.
2. Adhesives: VAE Emulsions Are Frequently Used In The Production Of Adhesives And Sealants. They Provide Excellent Adhesion To a Wide Range Of Substrates, Making Them Suitable For Applications Such As Woodworking, Paper Bonding, And Construction Adhesives.
3. Paints And Coatings: VAE Emulsions Are Employed As Binders In Water-Based Paints And Coatings. They Contribute To The Film-Forming Properties Of These Products, Enhancing Their Durability,

Adhesion, And Flexibility. They Are Also Known For Their Low Voc (Volatile Organic Compound) Content, Making Them Environmentally Friendly.

4. Textile Industry: In The Textile Industry, VAE Emulsions Are Utilized For Textile Coatings To Improve The Fabric's Water And Stain Resistance. They Also Enhance The Durability Of Printed Patterns.

5. Paper Industry: VAE Emulsions Are Used In Paper Coatings To Improve The Printability, Surface Finish, And Ink Holdout Properties Of Paper Products.

6. Construction: VAE Emulsions Find Applications In Construction Materials, Including Cement And Mortar Modifiers, Where They Improve Workability, Adhesion, And Durability.

7. Non-Woven Fabrics: VAE Emulsions Are Used In The Production Of Non-Woven Fabrics, Providing Strength And Flexibility To The Materials.

8. Emulsion Polymerization: They Serve As a Key Component In The Emulsion Polymerization Process To Produce Other Types Of Polymers And Latex Products.

Package:

Packages: In 25KG/50KG/220KG drum or 1000KG IBC drum.

Storage:

Store in accordance with local regulations on safe storage of chemical products.

Store in a dry, well-ventilated place. Stay away from hot objects, sparks, and other sources of ignition.

Incompatible with strong oxidants.